QUALITY. VALUE. ECONOMIC GROWTH.
WWW.MIAMIDADE.GOV/WATER

MIAMI-DADE COUNTY

Product Specifications

Miami-Dade Water & Sewer Department
Address: 3071 SW 38th Ave, Miami, FL 33146
Phone: (305) 665-7477

Plug Valve

Minimum Standards

- AWWA C507, C517, C606
- ANSI/AWWA: C111/A21.11; ANSI B16.1; ASTM: A126 Class B, A536 Grade 65-45-12, A123, A153
- MDWASD Specifications: Sections 15100, 15125

Other Requirements

- Non Lubricated Eccentric Type with Resilient Faced Plugs
- Minimum Working Pressure : 150psi =< 36" diameter
- All plug valves 8-inches and larger shall be full port – 100% Port Area
- 80% Port Area allowed for valves 6" and smaller only at locations away from Lift Station

Applications

- Sewer

PRE-APPROVED MANUFACTURER

1) Clow
2) Dezurik
3) Golden Anderson (GA)
4) Pratt
5) Val-Matic
6) Kennedy

Issue Date: 4/4/2016

Revised Date: 9/9/2016

APPROVED PRODUCTS / MODELS

SIZE	MANUFACTURER	MODEL	SUBMITTED
4" - 24"	Clow	F-5412 Eccentric Plug Valves FLG	☐
4" - 24"	Clow	F-5413 Eccentric Plug Valves MJ	☐
4" - 48"	Dezurik	PEF 100% Port Eccentric Plug Valves	☐
4" - 30"	Dezurik	PEC Eccentric Plug Valves	☐
4" - 30"	Golden Anderson (GA)	ECO-Centric Plug Valves	☐
4" - 36"	Pratt	Pratt Ballcentric Plug Valves Full Port	☐
4" - 30"	Val-Matic	Series 5600 or 5800 Eccentric Plug Valves	☐
4" - 30"	Val-Matic	Series 5700 or 5900 Port (Cam –Centric)	☐
4" - 48"	Kennedy	Kennedy Full Port Rectangular Plug Valve	☐

SIZE FURNISHED:

- ☐ 4"
- ☐ 6"
- ☐ 8"
- ☐ 10"
- ☐ 12"
- ☐ 14"
- ☐ 16"
- ☐ 18"
- ☐ 20"
- ☐ 24"
- ☐ 30"
- ☐ Other

COMMENTS: _____

_____
_____
_____

APPROVED PRODUCTS / MODELS		Plug	
SIZE	MANUFACTURER	MODEL	SUBMITTED

Approved by: David Vazquez, PE

Title: Specifications Manager